


 PRECISION MICRODRIVES

DESCRIPTION: 206-104

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS
TOLERANCES:
LINEAR: ±0.2
ANGULAR: ±1°3RD ANGLE PROJECTION


DO NOT SCALE DRAWING

DRAWING: 206-104

A4

REVISION: | SHEET 1 OF 1

	Samples available				
	Units	206-104			

Design and Accessories

1	Commutation	Precious Metal Brush
2	No. of Output Shafts	1
3	Unit Weight	g 4.5
4	Body Diameter	mm 6
5	Body Length	mm 30.6
6	Rotation Direction	CW
7	Bearing Type	Sintered Bronze

Physical Characteristics

8	Shaft Diameter	mm	1.5
9	Shaft Length	mm	6
10	Shaft Orientation		Inline
11	Motor Construction		Coreless

Operational Characteristics

12	Rated Operating Voltage	V	3
13	Rated Load	mN·m	1
14	Rated Load Speed	rpm	480
15	N/L Speed	rpm	1,100
16	Max. Start Voltage	V	1
17	Max. N/L Current	mA	80
18	Max. Operating Voltage	V	3.6
19	Max. Rated Load Current	mA	160
20	Min. Insulation Resistance	MΩ	1
21	Max. Start Current	mA	250
22	Typical Rated Load Power Consumption	mW	390
23	Typical N/L Current	mA	60
24	Typical Peak Efficiency	%	16
25	Typical Peak Eff. Torque	mN·m	0.75
26	Typical Peak Eff. Speed	rpm	720
27	Typical Peak Eff. Current	mA	115
28	Typical Peak Eff. Power Out	mW	55
29	Typical Start Current	mA	220

30	Typical Max. Output Power	mW	60
31	Typical Stall Torque	mN·m	2

Gear Characteristics

32	Gear Ratio	:	1	13.7
33	Gearhead Type			Planetary

Leads & Connectors Characteristics

34	Lead Length	mm	100
35	Lead Wire Gauge	AWG	32
36	Lead Configuration		Straight
37	Lead Strip Length	mm	1.5

Winding Characteristics

38	Typical Terminal Resistance	Ohm	13.2
39	Typical Terminal Inductance	uH	100

Environmental Characteristics

40	Max. Operating Temp.	°C	60
41	Min. Operating Temp.	°C	-10
42	Max. Storage & Transportation Temp.	°C	70
43	Min. Storage & Transportation Temp.	°C	-20

Packaging

44	No. of Units per Carton	pcs	2,000
45	Carton Type		Boxed Trays

Motor Body Characteristics**Performance**