



		Samples available	
		Units	212-105
Design and Accessories			
1	Commutation		Precious Metal Brush
2	No. of Output Shafts		1
3	Unit Weight	g	9.5
4	Body Diameter	mm	12
5	Body Length	mm	24
6	Rotation Direction		CCW
7	Bearing Type		Sintered Bronze
Physical Characteristics			
8	Shaft Diameter	mm	3
9	Shaft Length	mm	8
10	Shaft Orientation		Inline
11	Motor Construction		Iron Core
Operational Characteristics			
12	Typical Max. Mech. Noise	dB(A)	60
13	Rated Operating Voltage	V	3
14	Rated Load	mN·m	15
15	Rated Load Speed	rpm	62
16	N/L Speed	rpm	100
17	Max. Start Voltage	V	0.8
18	Max. N/L Current	mA	56
19	Max. Operating Voltage	V	3.6
20	Max. Rated Load Current	mA	149
21	Min. Insulation Resistance	MOhm	1
22	Max. Start Current	mA	335
23	Typical Rated Load Power Consumption	mW	450
24	Typical N/L Current	mA	47
25	Typical Peak Efficiency	%	32
26	Typical Peak Eff. Torque	mN·m	15
27	Typical Peak Eff. Speed	rpm	76
28	Typical Peak Eff. Current	mA	126
29	Typical Peak Eff. Power Out	mW	123

30	Typical Start Current	mA	335
31	Typical Max. Output Power	mW	157
32	Typical Stall Torque	mN-m	40

Gear Characteristics

33	Gear Ratio	:1	99
34	Gearhead Type		Spur

Winding Characteristics

35	Typical Terminal Resistance	Ohm	6.5
36	Typical Terminal Inductance	uH	1,100

Environmental Characteristics

37	Max. Operating Temp.	°C	50
38	Min. Operating Temp.	°C	-10
39	Max. Storage & Transportation Temp.	°C	80
40	Min. Storage & Transportation Temp.	°C	-40

Packaging

41	No. Units per Carton	pcs	500
42	Carton Type		Boxed Trays

Motor Body Characteristics

43	No. of Poles		
44	Shaft Axial Float	mm	
45	Max. Axial Compression	N	
46	Max. Radial Load	mN	

Performance

